

***Sun*** ELECTRIC CORPORATION  
**INSTALLATION  
INSTRUCTIONS**

**SPEEDOMETERS**

CP7656 (0-120M.P.H.)  
CP7657 (0-85M.P.H.)

Your Sun speedometer is a precision instrument that may be installed in any vehicle that has O.E.M. speedometer cable with a 5/8-18 connection and a .105 inch square drive. It has the added feature of a 99,999 mile odometer and is illuminated for night driving.

**INSTALLATION**

To mount your speedometer, a 3 3/8 inch hole is required. Install the speedometer in the hole and slide the mounting bracket over the studs on the rear of the case. The lockwashers and nuts provided are then threaded onto the studs and tightened securely. Once the speedometer has been mounted, the cable connection is threaded onto the rear of the unit and hand tightened securely.

**LIGHTING**

Connect the wire which is attached to the lamp socket to the vehicles light circuit. This enables one to utilize the dash dimmer control for the speedometer. Connect a wire (18 gauge insulated stranded copper wire, not included) from the nut holding down the mounting bracket to a good engine or chassis ground. Avoid painted or insulated surfaces. The lamp assembly snaps into the hole on the rear of the speedometer.

***Sun*** ELECTRIC CORPORATION  
INSTRUMENT PRODUCTS DIVISION  
1560 Trimble Road  
San Jose, California 95131

0692-5065CP

Printed in Taiwan